

# Crown Resources



2694 Hayes Wilbanks Road  
Toccoa, GA 30577  
(864)968-0592

## Geotextile Product Description Sheet

# Style C040

## Asphalt Overlay Fabric

C040 is a asphalt overlay nonwoven fabric produced by needlepunching synthetic staple fibers in a random network to form a high strength dimensionally stable fabric. The fibers are specially formulated to resist ultraviolet light deterioration. The fabric will not rot or mildew, is non-biodegradable, and is resistant to damage from insects and rodents. C040 conforms to the physical property values listed below:

Fabric Property	Test Method	Units	Minimum Average Roll Value
Weight	ASTM D 5261	oz/sqyd	4.1 (140 gm/sqm)
Grab Tensile	ASTM D 4632	lbs	101 (.45 kN)
Grab Elongation	ASTM D 4632	%	50
Asphalt Retention		gal/sqyd	.2
Melting Point		F	325 (163 C)
UV Resistance after 500 hrs.	ASTM D 4355	% Strength Retained	70

Packaging	
Roll Dimensions-Feet	12.5/15 x 360
Square Yards Per Roll	500/600
Estimated Roll Weight-Lbs.	160/190

To the best of our knowledge, the information contained herein is accurate. However, Crown Resources cannot anticipate all conditions under which product information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety or suitability of our products either alone or in combination with other products. Final determination of the suitability of any information or material for the use contemplated, of its manner of use, and whether the suggested use infringes any patents is the sole responsibility of the user.